

DX-D 40

The DX-D 40* Digital Detector with Automatic Exposure Detection (AED) offers a fast and effective way for radiography facilities to benefit from high quality digital imaging using any X-ray equipment.

- The easiest and most versatile way to go Direct Digital
- Automatic Exposure Detection (AED) allows seamless use with virtually all X-ray systems, maximizing the use of the existing X-ray equipment
- Improved workflow and exam speed
- Cassette-sized detector gives maximum convenience and portability
- Superior connectivity with DICOM compatible software and imagers
- MUSICA processing for excellent contrast detail and exam-independent, consistent image quality
- Choice of Cesium Iodide (CsI) or Gadolinium Oxy-Sulphide (GOS) detector conversion screens

The easiest way to go “instant DR”

For both conventional and mobile digital X-ray systems, the DX-D 40 Digital Detector offers general radiography facilities all the advantages of Direct Digital, while maximizing the use of their existing equipment. The Automatic Exposure Detection (AED) means no electrical connection to the X-ray system is required, for seamless use with virtually all X-ray systems.

At 43 x 35 cm in size, the detector fits into any standard bucky tray and can be easily removed to ensure versatility for all exams. Wireless technology enhances operator comfort, and improves exam flexibility and convenience, even in challenging imaging situations.

Faster and more efficient workflow

The DX-D 40 is an integral part of an Agfa HealthCare Instant DR solution, which includes the NX image acquisition software with MUSICA processing and detector. These cassette-less and filmless solutions provide a range of workflow benefits that improve productivity and speed up exam time. Retakes can be made immediately without changing cassette, and the number of images is no longer limited by the availability of cassettes. To complete the workflow, images can be sent immediately to a PACS or imager in DICOM format.





MUSICA and DR image quality: improved diagnostic confidence

The DX-D 40 is compatible with our 'gold standard' MUSICA image processing, which has been specially adapted and tuned to further enhance the excellent DR image quality. Exam-independent, it delivers consistent image quality and high contrast detail.

Combining MUSICA with the high quality of the DX-D 40, in terms of both sensitivity and sharpness, provides improved diagnostic confidence and efficiency.

Services & Support

Agfa HealthCare offers service agreement solutions tailored to the customer's situation. Available in Basic, Comfort and Advanced levels, they make your lifecycle costs predictable. A worldwide team of some 1,000 service professionals can provide support at all phases of your project, and even help customize your examination tree or link RIS protocol codes, further improving your return on investment. This team goes well beyond maintenance support, offering value-added services such as super user training, staff training and software upgrades.

Both extended warranty and drop insurance options are available for the DX-D 40.

Technical Specifications

DETECTOR

- **Detector type:** Amorphous Silicon with TFT
- **Conversion screen:** Csl and GOS
- **Pixel pitch:** 140 µm
- **Active pixel matrix:** 2560 x 3072 pixels
- **Active area size:** 358.4 mm x 430.1 mm
- **Effective pixel matrix:**
 - Csl: 2548 x 3060
 - GOS: 2560 x 3072
- **Effective area:**
 - Csl: 356.7 mm x 428.4 mm
 - GOS: 358.4 mm x 430.1 mm
- **Grayscale:** 14 bit
- **Spacial Resolution:** Min. 3.5 lp/mm
- **Outer dimensions:**
384 mm × 460 mm × 15 mm (ISO 4090)
- **Weight:**
 - Csl: 3.4 kg
 - GOS: 3.3 kg
- **Wireless data transmission:**
IEEE 802.1111a/b/g/n, 2.4 GHz/5 GHz,
- **Energy Range Standard:** 40 – 150 kVp

Environmental Requirements

Operation

- **Temperature:** +10 ~ +35° C
- **Humidity:** 30 ~ 85% (Non-condensing)
- **Atmospheric pressure:** 70 ~ 106 kPa
- **Shock:** 1.6 G
- **Vibration:** 0.7 G
- **Drop limits:** Max. 700 mm

Storage and transportation

- **Temperature:** -15 ~ +55° C
- **Humidity:** 10 ~ 90% (Non-Condensing)
- **Atmospheric pressure:** 50 ~ 106 kPa
- **Shock:** 20 G
- **Vibration:** 0.7 G
- **Drop limits:** Max. 700 mm

BATTERY SPECIFICATIONS

- **Type:** Lithium Ion Polymer Battery
- **Capacity:** 4000 mAh
- **Nominal Voltage:** 7.4V
- **Charging time:** 2 Hours
- **Operation time:**
4 hours (when sleep mode is off)
- **Cycle life:** Approx. 500 cycles,
Capacity ≥ 80% (100% = 4,000 mAh)

SYSTEM CONTROL UNIT

Power supply

- **Input:** AC100 to 240V, 50/60 Hz, Max. 200VA
- **Output:** DC +24V 3.3A, 80W

Cabling ports

- Gigabit Ethernet Ports – 3EA
- Power over Ethernet Ports – 2EA
- **Wireless communications:**
IEEE 802.11a/b/g/n (2.4 GHz/5 GHz)
- **Dimensions (W × H × D):**
300 mm × 235.8 mm × 58 mm,
Antenna height – 105 mm
- **Weight:** 2.5 kg

Environmental Requirements

Operation

- **Temperature:** +10 ~ +35° C
- **Humidity:** 30 ~ 85% (Non-condensing)
- **Atmospheric pressure:** 70 ~ 106 kPa

Storage and transportation

- **Temperature:** -15 ~ +55° C
- **Humidity:** 10 ~ 90% (Non-Condensing)
- **Atmospheric pressure:** 50 ~ 106 kPa

DIGITAL AED DETECTOR

Insight. Delivered.

Agfa HealthCare is a global leader in the fast growing market of integrated IT and imaging systems, offering healthcare facilities a seamless flow of information and a 360° view of patient care. The company has a unique, holistic approach, enabling it to provide in-depth clinical know-how and fully integrated hospital-wide solutions. These specialized solutions integrate IT and imaging systems for Radiology, Cardiology, Mammography, Orthopaedics and Veterinary Care. Agfa HealthCare's enterprise-wide IT platform integrates all administrative and clinical data within a healthcare facility and is designed to match the unique needs of specific healthcare professionals. ■

www.agfahealthcare.com

Agfa and the Agfa rhombus are trademarks of Agfa-Gevaert N.V., Belgium, or its affiliates. DX-D and MUSICA are trademarks of Agfa HealthCare NV, Belgium or its affiliates. All rights reserved. All other trademarks are held by their respective owners and are used in an editorial fashion with no intention of infringement. The data in this publication are for illustration purposes only and do not necessarily represent standards or specifications, which must be met by Agfa HealthCare. All information contained herein is intended for guidance purposes only, and characteristics of the products and services described in this publication can be changed at any time without notice. Products and services may not be available for your local area. Please contact your local sales representative for availability information. Agfa HealthCare diligently strives to provide as accurate information as possible, but shall not be responsible for any typographical error.

* Not available in US and Canada

© 2014 Agfa HealthCare NV
All rights reserved
Published by Agfa HealthCare NV
B-2640 Mortsel - Belgium
52T4J GB 00201407

AGFA 
HealthCare